

# Instructions: [Osborne's Barnacle Dissolver](#)

**\*\*DO NOT USE ON BARE ALUMINUM.**

**\*\*FOLLOW INSTRUCTIONS ON THE LABEL AND WEAR GLOVES AND EYE PROTECTION.**

## For propeller cleaning

For optimum results: (REPEAT BELOW ON EACH SECTION BEING CLEANED)

1. Spray the area to be cleaned with water before applying **Osborne's barnacle dissolver** product.
2. Twist the spray lock on the bottle to the spray position by pushing down on the yellow plastic pin and turning the end of the nozzle at the same time; selecting the desired spray pattern (wide or narrow)
3. Spray the product onto the surface to be cleaned and allow to sit for 30 seconds to 1 minute. Work in small sections (1 face of 1 propeller blade at a time) .
4. Use a suitable metal scraper to remove the bulk of the marine growth and barnacles re-spraying as needed until the surface is basically free of materials.
5. Rinse well with water
6. Re-spray the area with Barnacle Dissolver and then scrub vigorously with 3M Stripping pad (or similar)
7. Re-spray the area with Barnacle Dissolver and then polish with a 60 grit sanding sponge.
8. RINSE WELL WITH WATER



*If product gets chilled it may separate. If this happens simply shake and let stand until the product dissolves fully into solution again.*